

Technical specifications : Ref. 67110000

Number of leds								96
Power	W							250
Pre-programmed dimming								No
Control interface								1-10V
Optic type options		S20	S40	S60	S90	AF1		
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens		
Color temperature options		2200K	2700K	3000K	4000K	5000K	5700K	
Luminous flux	lm	30536	33051	34129	35925	35925	35925	
Lighting efficiency	lm/W	122.1	132.2	136.5	143.7	143.7	143.7	
LED current	mA	400	400	400	400	400	400	
Duration	h							100000
Working life								L90B10
Constant light output (CLO)								No
Standard Deviation Colour Matching (SDCM)								< 3
Color rendering index (CRI)								70
CE Mark								Yes
ENEC Certificate								No
Protection Class IEC								Class I
EU RoHS Compliant								Yes
IK Rating (light module)								10
IK Rating (whole luminaire)								10
IP Rating (light module)								66
IP Rating (whole luminaire)								66
Color								Aluminium
Material								Aluminium
Material cover								Without cover
Fixation Material								Aluminium
Mounting method (Floodlights)								Wall / Traverse / Pedestal/Floor
Surface protection								Anodized
Surface facing the wind	m ²							0.126
Number of LED modules								1
Minimum power factor								0.9500
Lighting source type								LED
Replaceable light source								Yes
Cable								Yes
Power consumption tolerance	%							5
Lighting flux tolerance	%							8
Electric connection								3-pole waterproof connector
Inrush current	A							0.77
Input voltage Max	Vac							240
Input voltage Min	Vac							220
Mains frequency								50 Hz
Total harmonic distortion (THD)								10
Max. Operating temperature	°F							104
Min. Operating temperature	°F							-31