Tekniska specifikationer : Ref. 67110700

Number of leds		384					
Power	W	1200					
Pre-programmed dimming		No					
Control interface		1-10V					
Optic type options		S20	S40	S60	S90	AF1	
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	
Color temperature options		2200K	2700K	3000K	4000K	5000K	5700K
Luminous flux	lm	146574	158645	163818	172440	172440	172440
Lighting efficiency	lm/W	122,1	132,2	136,5	143,7	143,7	143,7
LED current	mA	400	400	400	400	400	400
Duration	h	100000					
Working life		L90B10					
Constant ligh output (CLO)		No					
Standard Deviation Colour Matching (SDCM)		< 3					
Color rendering index (CRI)		70					
CE Mark		Yes					
ENEC Certificate		No					
Protection Class IEC		Class I					
EU RoHS Compliant		Yes					
IK Rating (light module)		10					
IK Rating (whole luminaire)		10					
IP Rating (light module)		66					
IP Rating (whole luminaire)		66					
Colour		Aluminum					
Material		Aluminium					
Material cover		Without cover					
Fixation Material		Aluminium					
Mounting method (Floodlights)		Wall / Traverse / Pedestal/Floor					
Surface protection		Anodized					
Surface facing the wind	m^2	0,3957					
Number of LED modules		4					
Minimum power factor		0.9500					
Lighting source type		LED					
Replaceable light source		Yes					
Cable		Yes					
Power consumption tolerance	%	5					
Lighting flux tolerance	%	8					
Electric connection		3-pole waterproof connector					
Inrush current	A	0,77					
Input voltage Max	Vac	240					
Input voltage Min	Vac	220					
Mains frequency		50 Hz					
Total harmonic distortion (THD)		10					
Max. Operating temperature	°C	40					
Min. Operating temperature	°C	-35					