

Technical specifications : Ref. 67112000

Number of leds					96				
Power	W				250				
Pre-programmed dimming					Yes				
Control interface					Dali 2				
Optic type options		S20	S40	S60	S90	AF1			
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens			
Color temperature options		2200K	2700K	3000K	4000K	5000K	5700K		
Luminous flux	lm	30536	33051	34129	35925	35925	35925		
Lighting efficiency	lm/W	122.1	132.2	136.5	143.7	143.7	143.7		
LED current	mA	400	400	400	400	400	400		
Duration	h				100000				
Working life					L90B10				
Constant light output (CLO)					No				
Standard Deviation Colour Matching (SDCM)					< 3				
Color rendering index (CRI)					70				
CE Mark					Yes				
ENEC Certificate					No				
Protection Class IEC					Class I				
EU RoHS Compliant					Yes				
IK Rating (light module)					10				
IK Rating (whole luminaire)					10				
IP Rating (light module)					66				
IP Rating (whole luminaire)					66				
Color					Aluminum				
Material					Aluminium				
Material cover					Without cover				
Fixation Material					Aluminium				
Mounting method (Floodlights)					Wall / Traverse / Pedestal/Floor				
Surface protection					Anodized				
Surface facing the wind	m²				0.126				
Number of LED modules					1				
Minimum power factor					0.9500				
Lighting source type					LED				
Replaceable light source					Yes				
Cable					Yes				
Power consumption tolerance	%				5				
Lighting flux tolerance	%				8				
Electric connection					3-pole waterproof connector				
Inrush current	A				0.77				
Input voltage Max	Vac				240				
Input voltage Min	Vac				220				
Mains frequency					50 Hz				
Total harmonic distortion (THD)					10				
Max. Operating temperature	°F				104				
Min. Operating temperature	°F				-31				