

Tekniska specifikationer : Ref. 68230001

Number of leds												36
Power	W											78
Pre-programmed dimming												Yes
Control interface												1-10V
Optic type options		P	T2	T3	ME	APZ	SCL	T4				
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens				
Color temperature options		2200K		2700K		3000K		4000K				PC Amber
Luminous flux	lm	9360		10140		10530		11700				4836
Lighting efficiency	lm/W	120		130		135		150				62
LED current	mA	330		330		330		330				660
Duration	h					100000						
Working life						L90B10						
Constant light output (CLO)						No						
Standard Deviation Colour Matching (SDCM)						< 3						
Color rendering index (CRI)						70						
CE Mark						Yes						
ENEC Certificate						Yes						
Protection Class IEC						Class II						
EU RoHS Compliant						Yes						
IK Rating (light module)						10						
IK Rating (whole luminaire)						10						
IP Rating (light module)						68						
IP Rating (whole luminaire)						66						
Colour						Aluminium						
Material						Aluminium						
Material cover						Without cover						
Fixation Material						Aluminium						
Mast diameter Max	mm					60						
Mast diameter Min	mm					42						
Mounting method						Post top/side entry						
Surface facing the wind	m ²					0,084						
Number of LED modules						3						
Minimum power factor						0.9500						
Lighting source type						LED						
Replaceable light source						Yes						
Cable						Yes						
Power consumption tolerance	%					5						
Lighting flux tolerance	%					8						
Electric connection						3-pole waterproof connector						
Inrush current	A					54						
Input voltage Max	Vac					240						
Input voltage Min	Vac					220						
Mains frequency						50 Hz						
Max. Operating temperature	°C					40						
Min. Operating temperature	°C					-35						