

Tekniska specifikationer : Ref. 68230200

Number of leds											36
Power	W										77
Pre-programmed dimming											Yes
Control interface											Dali 2
Optic type options		P	T2	T3	ME	APZ	SCL	T4			
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens			
Color temperature options		2200K		2700K		3000K		4000K			PC Amber
Luminous flux	lm	9240		10010		10395		11550			4774
Lighting efficiency	lm/W	120		130		135		150			62
LED current	mA	330		330		330		330			660
Duration	h					100000					
Working life						L90B10					
Constant light output (CLO)						Yes					
Standard Deviation Colour Matching (SDCM)						< 3					
Color rendering index (CRI)						70					
CE Mark						Yes					
ENEC Certificate						No					
Protection Class IEC						Class II					
EU RoHS Compliant						Yes					
IK Rating (light module)						10					
IK Rating (whole luminaire)						10					
IP Rating (light module)						68					
IP Rating (whole luminaire)						66					
Colour						Aluminium					
Material						Aluminium					
Material cover						Without cover					
Fixation Material						Aluminium					
Mast diameter Max	mm					60					
Mast diameter Min	mm					42					
Mounting method						Post top/side entry					
Surface facing the wind	m ²					0,084					
Number of LED modules						3					
Minimum power factor						0.9500					
Lighting source type						LED					
Replaceable light source						Yes					
Cable						Yes					
Power consumption tolerance	%					5					
Lighting flux tolerance	%					8					
Electric connection						3-pole waterproof connector					
Inrush current	A					54					
Input voltage Max	Vac					240					
Input voltage Min	Vac					220					
Mains frequency						50 Hz					
Max. Operating temperature	°C					40					
Min. Operating temperature	°C					-35					