

## Tekniska specifikationer : Ref. 70000000

|                                           |      |       |       |  |       |       |                             |
|-------------------------------------------|------|-------|-------|--|-------|-------|-----------------------------|
| Number of leds                            |      |       |       |  |       |       | 12                          |
| Power                                     | W    |       |       |  |       |       | 15                          |
| Pre-programmed dimming                    |      |       |       |  |       |       | No                          |
| Control interface                         |      |       |       |  |       |       | ON/OFF                      |
| Optic type options                        |      |       |       |  |       |       | SP                          |
| Lens type                                 |      |       |       |  |       |       | PC protector                |
| Color temperature options                 |      | 2200K | 2700K |  | 3000K | 4000K | PC Amber                    |
| Luminous flux                             | lm   | 675   | 720   |  | 750   | 810   | 330                         |
| Lighting efficiency                       | lm/W | 45    | 48    |  | 50    | 54    | 22                          |
| LED current                               | mA   | 200   | 200   |  | 200   | 200   | 400                         |
| Duration                                  | h    |       |       |  |       |       | 100000                      |
| Working life                              |      |       |       |  |       |       | L90B10                      |
| Constant ligh output (CLO)                |      |       |       |  |       |       | No                          |
| Standard Deviation Colour Matching (SDCM) |      |       |       |  |       |       | < 3                         |
| Color rendering index (CRI)               |      |       |       |  |       |       | 70                          |
| CE Mark                                   |      |       |       |  |       |       | Yes                         |
| ENEC Certificate                          |      |       |       |  |       |       | No                          |
| Protection Class IEC                      |      |       |       |  |       |       | Class II                    |
| EU RoHS Compliant                         |      |       |       |  |       |       | Yes                         |
| IK Rating (light module)                  |      |       |       |  |       |       | 10                          |
| IK Rating (whole luminaire)               |      |       |       |  |       |       | 10                          |
| IP Rating (light module)                  |      |       |       |  |       |       | 66                          |
| IP Rating (whole luminaire)               |      |       |       |  |       |       | 65                          |
| Colour                                    |      |       |       |  |       |       | Inox                        |
| Material                                  |      |       |       |  |       |       | stainless steel             |
| Housing material quality                  |      |       |       |  |       |       | AlSI 304                    |
| Material cover                            |      |       |       |  |       |       | Opaque plastic              |
| Mounting method                           |      |       |       |  |       |       | Other                       |
| Surface protection                        |      |       |       |  |       |       | Lacquered                   |
| Surface facing the wind                   | m²   |       |       |  |       |       | 0,065                       |
| Number of LED modules                     |      |       |       |  |       |       | 1                           |
| Minimum power factor                      |      |       |       |  |       |       | 0.9500                      |
| Lighting source type                      |      |       |       |  |       |       | LED                         |
| Replaceable light source                  |      |       |       |  |       |       | Yes                         |
| Cable                                     |      |       |       |  |       |       | Yes                         |
| Power consumption tolerance               | %    |       |       |  |       |       | 5                           |
| Lighting flux tolerance                   | %    |       |       |  |       |       | 8                           |
| Electric connection                       |      |       |       |  |       |       | 3-pole waterproof connector |
| Inrush current                            | A    |       |       |  |       |       | 26                          |
| Input voltage Max                         | Vac  |       |       |  |       |       | 240                         |
| Input voltage Min                         | Vac  |       |       |  |       |       | 220                         |
| Mains frequency                           |      |       |       |  |       |       | 50 Hz                       |
| Max. Operating temperature                | °C   |       |       |  |       |       | 40                          |
| Min. Operating temperature                | °C   |       |       |  |       |       | -35                         |