

Technical specifications : Ref. 70001000

Number of leds							12
Power	W						24
Pre-programmed dimming							No
Control interface							ON/OFF
Optic type options							SP
Lens type							PC protector
Color temperature options		2200K	2700K		3000K	4000K	PC Amber
Luminous flux	lm	912	960		1008	1080	456
Lighting efficiency	lm/W	38	40		42	45	19
LED current	mA	200	200		200	200	400
Duration	h				100000		
Working life					L90B10		
Constant light output (CLO)					No		
Standard Deviation Colour Matching (SDCM)					< 3		
Color rendering index (CRI)					70		
CE Mark					Yes		
ENEC Certificate					No		
Protection Class IEC					Class II		
EU RoHS Compliant					Yes		
IK Rating (light module)					10		
IK Rating (whole luminaire)					10		
IP Rating (light module)					66		
IP Rating (whole luminaire)					65		
Color					Inox		
Material					stainless steel		
Housing material quality					AISI 304		
Material cover					Opaque plastic		
Mounting method					Other		
Surface protection					Lacquered		
Surface facing the wind	m ²				0.174		
Number of LED modules					1		
Minimum power factor					0.9500		
Lighting source type					LED		
Replaceable light source					Yes		
Cable					Yes		
Power consumption tolerance	%				5		
Lighting flux tolerance	%				8		
Electric connection					3-pole waterproof connector		
Inrush current	A				26		
Input voltage Max	Vac				240		
Input voltage Min	Vac				220		
Mains frequency					50 Hz		
Max. Operating temperature	°F				104		
Min. Operating temperature	°F				-31		