

Technical specifications : Ref. 67121100

| | | | | | | | | |
|---|----------------|---------|---------|---------|---------|---------|-------|----------------------------------|
| Number of leds | | | | | | | | 96 |
| Power | W | | | | | | | 300 |
| Pre-programmed dimming | | | | | | | | No |
| Control interface | | | | | | | | 1-10V |
| Optic type options | | S20 | S40 | S60 | S90 | AF1 | | |
| Lens type | | PC lens | PC lens | PC lens | PC lens | PC lens | | |
| Color temperature options | | 2200K | 2700K | 3000K | 4000K | 5000K | 5700K | |
| Luminous flux | lm | 36644 | 39661 | 40955 | 43110 | 43110 | 43110 | |
| Lighting efficiency | lm/W | 122.1 | 132.2 | 136.5 | 143.7 | 143.7 | 143.7 | |
| LED current | mA | 400 | 400 | 400 | 400 | 400 | 400 | |
| Duration | h | | | | | | | 100000 |
| Working life | | | | | | | | L90B10 |
| Constant light output (CLO) | | | | | | | | No |
| Standard Deviation Colour Matching (SDCM) | | | | | | | | < 3 |
| Color rendering index (CRI) | | | | | | | | 70 |
| CE Mark | | | | | | | | Yes |
| ENEC Certificate | | | | | | | | No |
| Protection Class IEC | | | | | | | | Class I |
| EU RoHS Compliant | | | | | | | | Yes |
| IK Rating (light module) | | | | | | | | 10 |
| IK Rating (whole luminaire) | | | | | | | | 10 |
| IP Rating (light module) | | | | | | | | 66 |
| IP Rating (whole luminaire) | | | | | | | | 66 |
| Color | | | | | | | | Aluminium |
| Material | | | | | | | | Aluminium |
| Material cover | | | | | | | | Without cover |
| Fixation Material | | | | | | | | Aluminium |
| Mounting method (Floodlights) | | | | | | | | Wall / Traverse / Pedestal/Floor |
| Surface protection | | | | | | | | Anodized |
| Surface facing the wind | m ² | | | | | | | 0.126 |
| Number of LED modules | | | | | | | | 1 |
| Minimum power factor | | | | | | | | 0.9500 |
| Lighting source type | | | | | | | | LED |
| Replaceable light source | | | | | | | | Yes |
| Cable | | | | | | | | Yes |
| Power consumption tolerance | % | | | | | | | 5 |
| Lighting flux tolerance | % | | | | | | | 8 |
| Electric connection | | | | | | | | 3-pole waterproof connector |
| Inrush current | A | | | | | | | 0.77 |
| Input voltage Max | Vac | | | | | | | 240 |
| Input voltage Min | Vac | | | | | | | 220 |
| Mains frequency | | | | | | | | 50 Hz |
| Total harmonic distortion (THD) | | | | | | | | 10 |
| Max. Operating temperature | °F | | | | | | | 104 |
| Min. Operating temperature | °F | | | | | | | -31 |