

Technical specifications : Ref. 532181

Number of inputs					6		
Number of outputs					1		
Bands		BI	FM	BIII	UHF	CATV	
Frequency range	MHz	54 ... 88	88 ... 108	174 ... 216	470 ... 698	54 ... 1218	
Number of filters		--	--	--	32	--	
Channels per filter		--	--	--	1 ... 4	--	
Gain	dB	75	30	75	75	40	
Gain adjustment range	dB	AGC	5 ... 30	AGC	AGC	10 ... 45	
Manual regulation after auto-adjustment	dB	-3 ... 3	-5 ... 5	-3 ... 3	-3 ... 3	--	
Slope regulation	dB	--	--	--	0 ... 8	20	
Input level	dBmV	-20 ... 40	15 ... 40	-20 ... 40	-20 ... 40	--	
Output level DIN45004B	dBmV	62	62	62	62	62	
Output level EN50083	dBmV	66	66	66	66	66	
Programmable output level	dBmV	30 ... 55	20 ... 45	30 ... 55	30 ... 55	--	
Noise figure	dB	9	--	7	6	8	
Selectivity	dB	> 50	> 20	> 50	> 50	--	
Powering per inputs	Vdc	12	--	12	12	--	
Max current input	mA	70	--	--	--	--	
Input voltage	Vac			110 ... 230			
Mains frequency				50 Hz / 60 Hz			
Max. current	mA			250			
Max. power consumption	W			14			
Protection index (IP)				20			
Operating temperature	°F			23 ... 113			