

Technical specifications : Ref. 414882

| | | | | | | | | | | | | | | | | | | | | | |
|---|------|-------------------------|--------|--------|--------|---------|---------|---------|---------|---------|---------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Model | | SK6Fplus | | | | | | | | | | | | | | | | | | | |
| Cable type | | RG-6 | | | | | | | | | | | | | | | | | | | |
| Standard | | EN50117-9-2 | | | | | | | | | | | | | | | | | | | |
| Euroclass | | Eca | | | | | | | | | | | | | | | | | | | |
| Class | | A+ | | | | | | | | | | | | | | | | | | | |
| Inner conductor Diameter | in | 0.04 | | | | | | | | | | | | | | | | | | | |
| Inner conductor Material | | Copper-clad steel (CCS) | | | | | | | | | | | | | | | | | | | |
| Inner conductor Resistance | Ω/km | < 110 | | | | | | | | | | | | | | | | | | | |
| Dielectric Diameter | in | 0.181 | | | | | | | | | | | | | | | | | | | |
| Dielectric Material | | Foam polyethylene (PEE) | | | | | | | | | | | | | | | | | | | |
| Dielectric Color | | White RAL 9003 | | | | | | | | | | | | | | | | | | | |
| Overlapped foil | | Aluminium + Polyester | | | | | | | | | | | | | | | | | | | |
| Braid Material | | Aluminium | | | | | | | | | | | | | | | | | | | |
| Braid dimensions: No. of carriers (Nc) | | 16 | | | | | | | | | | | | | | | | | | | |
| Braid Dimensions: No. of strands per carrier (Ns) | | 8 | | | | | | | | | | | | | | | | | | | |
| Braid Dimensions: strand diameter (Ø) | in | 0.006 | | | | | | | | | | | | | | | | | | | |
| Braid Resistance | Ω/km | < 30 | | | | | | | | | | | | | | | | | | | |
| Braid Coverage | % | 90 | | | | | | | | | | | | | | | | | | | |
| 2nd foil | | Yes | | | | | | | | | | | | | | | | | | | |
| 2nd foil glued to the dielectric | | No | | | | | | | | | | | | | | | | | | | |
| Petrol-Jelly | | No | | | | | | | | | | | | | | | | | | | |
| Anti-migrating film | | No | | | | | | | | | | | | | | | | | | | |
| Outer sheath Diameter | in | 0.268 | | | | | | | | | | | | | | | | | | | |
| Outer sheath Material | | LSFH, UV-resistant | | | | | | | | | | | | | | | | | | | |
| Minimum bending radius | in | 1.339 | | | | | | | | | | | | | | | | | | | |
| Transfer impedance (5-30MHz) | mΩ/m | < 2.5 | | | | | | | | | | | | | | | | | | | |
| 1GHz shielding | dB | > 95 | | | | | | | | | | | | | | | | | | | |
| Spark Test | Vac | 3000 | | | | | | | | | | | | | | | | | | | |
| Capacitance | pF/m | 53 | | | | | | | | | | | | | | | | | | | |
| Impedance | Ω | 75 | | | | | | | | | | | | | | | | | | | |
| Velocity ratio | % | 82 | | | | | | | | | | | | | | | | | | | |
| Operating temperature | °F | -22 ... 158 | | | | | | | | | | | | | | | | | | | |
| Frequencies | | 5 MHz | 47 MHz | 54 MHz | 90 MHz | 200 MHz | 500 MHz | 698 MHz | 800 MHz | 862 MHz | 950 MHz | 1000 MHz | 1220 MHz | 1350 MHz | 1750 MHz | 2050 MHz | 2150 MHz | 2200 MHz | 2300 MHz | 2400 MHz | 3000 MHz |
| Attenuation (typ.) | dB/m | 0.02 | 0.05 | 0.05 | 0.06 | 0.1 | 0.15 | 0.17 | 0.19 | 0.2 | 0.21 | 0.22 | 0.23 | 0.25 | 0.29 | 0.31 | 0.32 | 0.33 | 0.33 | 0.34 | 0.4 |
| Return losses (min.) | dB | 20 | 20 | 20 | 20 | 20 | 18 | 18 | 18 | 18 | 18 | 16 | 16 | 16 | 16 | 15 | 15 | 15 | 15 | 15 | 15 |