

Technical specifications : Ref. 63153100

Number of leds									24
Power	W								40
Pre-programmed dimming									No
Control interface									Dali 2
Optic type options		AS1	AS2	AS3		AS4	AS5	AS6	
Lens type		PC lens	PC lens	PC lens		PC lens	PC lens	PC lens	
Color temperature options		2200K	2700K	3000K		4000K	5000K	PC Amber	
Luminous flux	lm	4680	5120	5360		5720	5720	2400	
Lighting efficiency	lm/W	117	128	134		143	143	60	
LED current	mA	210	210	210		210	420	210	
Duration	h								100000
Working life									L90B10
Constant light output (CLO)									Yes
Standard Deviation Colour Matching (SDCM)									< 3
Color rendering index (CRI)									70
CE Mark									Yes
ENEC Certificate									No
Protection Class IEC									Class I
EU RoHS Compliant									Yes
IK Rating (light module)									10
IK Rating (whole luminaire)									10
IP Rating (light module)									68
IP Rating (whole luminaire)									66
Color									Black
Material									Aluminium
Material cover									Without cover
Fixation Material									Aluminium
Mounting method									Other
Surface protection									Powder coating
Number of LED modules									1
Minimum power factor									0.9500
Lighting source type									LED
Replaceable light source									Yes
Cable									Yes
Power consumption tolerance	%								5
Lighting flux tolerance	%								8
Electric connection									3-pole waterproof connector
Inrush current	A								1.57
Input voltage Max	Vac								240
Input voltage Min	Vac								220
Mains frequency									50 Hz
Max. Operating temperature	°F								104
Min. Operating temperature	°F								-31