Televes®

Tekniska specifikationer : Ref. 63153100

Number of leds		24					
Power	W	40					
Pre-programmed dimming		No					
Control interface		Dali 2					
Optic type options		AS1	AS2	AS3	AS4	AS5	AS6
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K	2700K	3000K	4000K	5000K	PC Amber
Luminous flux	lm	4680	5120	5360	5720	5720	2400
Lighting efficiency	lm/W	117	128	134	143	143	60
LED current	mA	210	210	210	210	210	420	210
Duration	h	100000					
Working life		L90B10					
Constant ligh output (CLO)		Yes					
Standard Deviation Colour Matching (SDCM)		< 3					
Color rendering index (CRI)		70					
CE Mark		Yes					
ENEC Certificate		No					
Protection Class IEC		Class I					
EU RoHS Compliant		Yes					
IK Rating (light module)		10					
IK Rating (whole luminaire)		10					
IP Rating (light module)		68					
IP Rating (whole luminaire)		66					
Colour		Black					
Material		Aluminium					
Material cover		Without cover					
Fixation Material		Aluminium					
Mounting method		Other					
Surface protection		Powder coating					
Number of LED modules		1					
Minimum power factor		0.9500					
Lighting source type		LED					
Replaceable light source		Yes					
Cable		Yes					
Power consumption tolerance	%	5					
Lighting flux tolerance	%	8					
Electric connection		3-pole waterproof connector					
Inrush current	A	1,57					
Input voltage Max	Vac	240					
Input voltage Min	Vac	220					
Mains frequency		50 Hz					
Max. Operating temperature	°C	40					
Min. Operating temperature	°C	-35					