

## Technical specifications : Ref. 63353100

Number of leds										48
Power	W									70
Pre-programmed dimming										No
Control interface										Dali 2
Optic type options										
Color temperature options		2200K	2700K	3000K	4000K	5000K	PC Amber			
Luminous flux	lm	8190	8960	9380	10010	10010	4200			
Lighting efficiency	lm/W	117	128	134	143	143	60			
LED current	mA	250	250	250	250	250	500	250		
Duration	h									100000
Working life										L90B10
Constant high output (CLO)										Yes
Standard Deviation Colour Matching (SDCM)										< 3
Color rendering index (CRI)										70
CE Mark										Yes
ENEC Certificate										No
Protection Class IEC										Class I
EU RoHS Compliant										Yes
IK Rating (light module)										10
IK Rating (whole luminaire)										10
IP Rating (light module)										68
IP Rating (whole luminaire)										66
Color										Black
Material										Aluminium
Material cover										Without cover
Fixation Material										Aluminium
Mounting method										Other
Surface protection										Powder coating
Number of LED modules										1
Minimum power factor										0.9500
Lighting source type										LED
Replaceable light source										Yes
Cable										Yes
Power consumption tolerance	%									5
Lighting flux tolerance	%									8
Electric connection										3-pole waterproof connector
Inrush current	A									2.15
Input voltage Max	Vac									240
Input voltage Min	Vac									220
Mains frequency										50 Hz
Max. Operating temperature	°F									104
Min. Operating temperature	°F									-31