

Technical specifications : Ref. 237507

| Inputs/Bands | | TERR | V | H |
|--------------------------------|------|---------------|------------------|--------------|
| Frequency range | MHz | 47 ... 694 | 290 ... 2340 | 290 ... 2340 |
| Input level | dBmV | 23 ... 35 | 10 ... 25 | 10 ... 25 |
| Powering per inputs | Vdc | 11.7 ... 17.7 | 11.7 ... 17.7 | -- |
| Max. current pass | mA | 500 | 500 | -- |
| Max. current pass total inputs | mA | | 720 | |
| Impedance | Ω | | 75 | |
| Laser | | | MQW-DFB uncooled | |
| Wavelength | nm | | 1530 | |
| Optical output power | dBm | | 9 | |
| RF connectors | | | "F" female | |
| Optical connectors | | | SC/APC | |
| Powering | Vdc | | 12 ... 18 | |
| Max. power consumption | W | | 5.6 | |
| Current consumption | mA | | < 430 | |
| Operating temperature | °F | | 23 ... 113 | |
| PSU input voltage | Vac | | 100 ... 240 | |
| Max PSU current input | mA | | 600 | |
| PSU output voltage | Vdc | | 12 | |
| Max PSU output current | A | | 1.5 | |