

Technical specifications : Ref. 232658

| | | |
|--------------------------------------|-------|-----------------------------|
| Euroclass | | Dca |
| Euroclass: Smoke Production | | s2 |
| Euroclass: Flaming droplets | | d2 |
| Euroclass: Acidity | | a1 |
| Fiber core type | | Single-mode (ITU-T-G.657A2) |
| Optical fiber type category | | OS1 |
| Fiber core diameter | µm | 9 |
| Fiber cladding diameter | µm | 125 |
| Coating buffer diameter | µm | 250 |
| Cable structure | | Tight buffer |
| Plastic buffer diameter | in | 0.033 |
| Outer sheath Diameter | in | 0.118 |
| Outer sheath Material | | LSFH |
| Blocking jelly | | No |
| Attenuation 1310nm | dB/km | < 0,8 |
| Attenuation 1490nm | dB/km | < 0,8 |
| Attenuation 1550nm | dB/km | < 0,8 |
| Insertion losses in connector 1 | dB | < 0,5 |
| Insertion losses in connector 2 | dB | < 0,5 |
| Return losses in connector 1 | dB | > 60 |
| Return losses in connector 2 | dB | > 60 |
| Optical connector type 1 | | SC |
| Polishing type (Optical connector 1) | | APC |
| Optical connector type 2 | | SC |
| Polishing type (Optical connector 2) | | APC |
| Short tension | N | 1000 |
| Long tension | N | 500 |
| Structure reinforcement element | | Aramid fibers |
| Short crush (@100mm) | N | 1000 |
| Long crush (@100mm) | N | 300 |
| Minimum bending radius | in | 0.591 |
| Operating temperature | °F | -4 ... 158 |